



MA3145 (4 Pole) Class II

Cost effective surge protection designed to cope with secondary currents as described in IEC 61312

- Space saving design, DIN-rail mounting
- Full range of AC mains power applications
- Coordinated surge protection to IEC 61312; rated according to IEC 61643
- Single module for three phase applications on TN-C-S systems



The MA3100 Series offers cost effective, DIN-rail mounted, surge protection for applications described by IEC 61312. The Class II range of surge arrestors fit in to the cascade philosophy along side Class I & Class III devices.


All modules are DIN-rail mounted for ease of installation and have very small footprints therefore minimising the space required. Each device is simply connected in parallel with the power.

The Class II surge current arrester is designed to work as both a standalone device and in cascade coordination with MTL's Class I lightning arrester. A 4 pole width module withstands surge currents up to 45,000 amps with 8/20µs waveform. The Class II arresters offer protection for three phase systems type TN-C-S. The 4 pole Class II arresters have remote monitoring capabilities as a standard feature. Voltage free, normally open, normally closed contacts can be used for a variety of monitoring tasks.

Coordinated IEC 61643 Class I, Class II and Class III surge protection


The MA3100 range offers cost effective surge protection for applications described by IEC 61312, where the AC mains supply can carry a partial share of the lightning surge current. Class I surge protectors (rated according to IEC 61643) are designed to carry up to 50kA (10/350µs). Class II surge protectors are characterized by their ability to protect against 8/20µs impulses up to 50kA, possibly resulting from the operation of a class I device. Finally Class III devices are used to protect individual pieces of equipment. An excellent example of a class III device is the MA15.

Cascade Effect Example




*Total over a 3 phase system

TN-C-S SYSTEM




MA3145-230-4-R




CLASS II SURGE PROTECTION DEVICE

Technical data	MA3145	230-4-R
Dimensions	See Figure 1	
IEC category/VDE requirement class:	II/C	
Nominal voltage U_n :	230/400V AC	
Max. continuous operating voltage U_c :	270V AC	
Lightning test current I_{imp} (10/350 μ s)	peak value/charge:	N.A.
	Q charge:	N.A.
Leakage current to PE at U_n :	≤ 0.3 mA	
Nominal discharge surge current I_n (8/20 μ s):	10kA	
Max. discharge surge current I_{max} (8/20 μ s):	45kA	
Protection level U_p :	1080V	
Residual voltage at 5kA:	900V	
Response time t_a :	≤ 25 ns	
Max. required backup fuse:	125A gL-type	
Remote indication contact: max. permitted operating voltage U_{max}	125V AC/110V DC	
	max. permitted operating current I_{max} AC or DC	0.3A
Temperature range:	-40°C to +80°C	
Protection type according to IEC 60 529/EN 60 529:	IP20	
Flammability class according to UL94:	VO	
Stripping length: Biconnect terminal blocks/remote indicator contact:	14.5/7mm	
Torque: Biconnect terminal blocks/remote indicator contact:	4.5Nm/0.25Nm	
Weight (typ.):	290g	
Approvals:		
Test standards: UL1449 2nd Edition; IEC 61643-1:1998-02		



To order Class I surge protection devices, specify -

MA31 45 230 4 R



R = Remote contacts present

4 = 4 module widths

230 = operating voltage

45 = Product series

MA31 = (Product range name)

The given data is only intended as a product description and should not be regarded as a legal warranty of properties or guarantee. In the interest of further technical developments, we reserve the right to make design changes.



EUROPE (EMEA): +44 (0)1582 723633
enquiry@mtl-inst.com

THE AMERICAS: +1 800 835 7075
csinfo@mtl-inst.com

ASIA-PACIFIC: +65 6 645 9888
sales.mtlsing@cooperindustries.com

901-172 RevA - 070411